

# Christie

## Access Series LCD panels

The perfect balance between performance and price

24/7 operation



Technical specifications		Christie UHD751-P	Christie UHD861-P
Display technology	screen size (diagonal)	• 75" (190.5cm)	• 86" (217.4cm)
	native resolution	• UHD 3840 x 2160 (16:9)	
	backlight	• Direct-lit LED	
	LED lifespan	• 50,000 hours to 50% brightness	
	display orientation	• Portrait or landscape	
	pixel pitch	• 0.429 x 0.429mm	• 0.493 x 0.493mm
	nominal bezel size (bottom/side/top)	• 38mm/16mm/16mm	• 103mm/30mm/30mm
	brightness	• 600 nits (cd/m <sup>2</sup> ) typical	• 500 nits (cd/m <sup>2</sup> ) typical
	contrast ratio (full field)	• 1200:1 typical	
	viewing angle (CR 10:1)	• 178° h/v	
	refresh rate	• 60Hz	• 120Hz
	response time	• 8ms typical	
	color space (CIE 1931)	• 75% typical	• 60% minimum
	display colors	• 10 bit, 1.07 billion colors	
Video	inputs	• 2 x HDMI™ (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3) • VGA • YPbPr • 2 x USB 2.0 • USB 3.0	
	outputs	• DisplayPort™ 1.2a; HDMI 2.0	
Audio	inputs	• RCA (L/R) line in	
	outputs	• RCA (L/R) line out • 3.5mm headphone jack • SPDIF coax	
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender	
Power	input rating	• 100-240 VAC @ 50-60Hz	
	power consumption	• 218W typical (without OPS) • 250W typical (without OPS) • <= 0.5W in standby (without OPS)	• 251W typical (without OPS) • 310W typical (without OPS) • <= 0.5W in standby (without OPS)
Environment	operating temperature	• 32-104°F (0-40°C)	
	storage temperature	• -4-140°F (-20-60°C)	
	operating humidity	• 20-90% RH non-condensing	
Physical	size (panel only)	• (WxHxD) 66.3 x 38.1 x 2.9" (1684 x 967 x 73mm)	• (WxHxD) 77.8 x 45.1 x 4.1" (1975 x 1146 x 103mm)
	weight	• 80.5lbs (36.5kg)	• 144.4lbs (65.5kg)
	mounting	• VESA 600 x 400mm, M6	
Runtime	• Designed for 24/7 operation featuring a reliable power supply <sup>1</sup>		
Features	• Commercial-grade LCD with LED backlight • OPS slot • Anti-glare treatment • 2 x 8W speakers • On/off scheduler • USB playback of Photo/Video/MP3 • HDMI-CEC • Source switching for failover • Kensington lock • Wi-Fi® • Bluetooth® • Miracast device connectivity • Pixel shifting		
Accessories	• Panel ships with IR remote control • External IR receiver • Power cable • User manual • Optional TA751 up to 10 point IR touch overlay (for 75" panel only)		
Warranty	• Three years parts and labor limited warranty • Contact an authorized Christie® representative for full details		

<sup>1</sup> Avoid static images for extended periods. Refer to the product documentation for additional guidance. Content and operating conditions can affect the useful life of the product. Please refer to the product documentation and Christie Operating Guidelines for Flat Panels, available at [www.christiedigital.com](http://www.christiedigital.com)

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2019 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. 4525 Nov 19



**CHRISTIE**®